

5G WIFI Wireless Digital Discussion Chairman Unit

TRI-ACV-MCW-4003

Large venues | Live events & performing arts | Auditorium | planetarium | Network Operation Centers

Features:

- Sleek, touch-interface with 2.23" OLED display for signal, battery, time/date, and timer.
- Quick installation and teardown.
- Built-in DC input and detachable battery (4-hour charge, 24-hour use).
- Built-in hi-fi speaker, pluggable long-range mic (various lengths), full-digital transmission free from RF interference.
- Auto MIC-off timer, software-configurable as Chairman or Delegate unit.

Functions:

- Standards Compliant IEC 60914, GBT 15381-94. Quick installation and teardown.
- Wi-Fi Compatibility Standard 5GHz Wi-Fi, supports over 40 wireless units per AP expandable via additional APs.
- User-Friendly Interface - Dual headset jacks, volume control
- Camera Integration auto-tracking via RS232/RS485 using PELCO/VISCA with HD PTZ camera support.
- Auto MIC-off timer, software-configurable as Chairman or Delegate unit.



TRI-ACV-MCW-4003

Technical specifications

Parameter	Value
Button	Touchable interface
Sound Pickup	heart type capacitance
Display	OLED display 128 × 32
Sensitivity	-46 DBV / Pa
Maximum power consumption	2.0W
Directivity	0 ° / 180 °> 20 dB (1 kHz)
Headphone load	16Ω
Headphone volume	10mW
Headphone jack	3.5mm stereo
Input impedance	2kΩ
SNR	70dB
Frequency response	20 ~ 20000Hz
Equivalent noise	20dBA (SPL)
Main material	ABS
Operating temperature	0 °C to + 55 °C
Color	Black
The maximum sound pressure	125dB (THD <3%)
Weight	1.1kg (with microphone)
Dimension	195L × 120W × 60Hmm (without microphone)

For the most current specification information, please visit tri-star.co.in