

Full digital interfacebox

TRI-ACV-MEXM-4044

Large venues | Live events & performing arts | Auditorium | planetarium | Network Operation Centers

Features:

- The full-digital interface box is a conference product specially designed to meet the special needs of the conference. The exterior is mini and lightweight, and the all-metal thin shell design can cope with any environment and can be easily installed under the table and table. Indirect seams or armrests can be connected to the hand microphone for conference environments without a conference table. Or when there is a need to customize a dedicated conference panel or a panel with special features, can meet the diverse needs of customers
- Built-in DSP digital sound processor, 48kHz High-quality sound sampling frequency for AGC function of the picked-up audio for devices such as gooseneck microphones on connected panels or handheld microphones. At the same time, it also has ANC function to filter out the noisy background audio in the conference space. Through the AFC function, the feedback problem can be processed effectively and quickly, avoiding the whistling of the microphone and affecting the quality of the conference. And can transmit high-definition loss less digital audio through digital audio processing technology
- For the panel of the chairman function: Provide the chairman function switch to turn off the delegate function.
- For the panel of the chairman function: Provide the chairman function switch to turn off the delegate function.
- When it is a panel of the function: Provide speaking switch.
- Provides speaker output function, which can be used to selectively set the conference system loudspeakers on the panel.
- Supports the speaking timing function, which automatically turns off the microphone when the speaking time is cut off.



TRI-ACV-MEXM-4044

Technical specifications

Parameter	Value
Maximum power consumption	2.0W
Frequency response	20~20kHz
Total Harmonic Distortion (THD)	<0.1%
Dynamic range	Dynamic range
Signal to noise ratio (S/N)	>96dB
Rated microphone input	>70dB SPL
Maximum microphone input	>100dB SPL
Speaker rated output	>70dB SPL at 0.5m
Sensitivity	-46 dBV/Pa
Connect:	
RJ-45 female seat	2
D-Sub 15 Pin	1
Color	Black
Weight	300g
size (mm)	100L x 60W x 24 H