

## Handheld Microphone

TRI-ACV-MHH-4043

Large venues | Live events & performing arts | Auditorium | planetarium | Network Operation Centers

### Features:

- LED ring indicator
- Heart-shaped pickup
- Rear electret condenser pickup
- Double rubber suspension pickup
- Highly close SPL level
- Low noise pickup
- Dual function switch
- Two-color LED



## TRI-ACV-MHH-4043

### Technical specifications

| Parameter                      | Value                   |
|--------------------------------|-------------------------|
| Pickup head                    | Back-electret condenser |
| Frequency response             | 50Hz~18kHz              |
| Power consumption              | 1.5 to 9 VDC            |
| Dynamic range                  | >94dB                   |
| Signal to noise ratio (S / N)  | <60 dBA                 |
| Maximum microphone input       | > 138 dB SPL            |
| THD                            | <0.1%                   |
| Speaker rated output           | > 70dB SPL at 0.5m      |
| Sensitivity                    | -68 dB±3dB /μBar        |
| Impedance                      | 2 kOhms @ 1 kHz         |
| connection:                    |                         |
| Mechanical connector           | 6-pin XLR male          |
| Color:                         |                         |
| Black Weight                   | 0.2kg                   |
| Dimensions (height x diameter) | 160 x 30mm              |