




# TRISTAR



[www.tri-star.co.in](http://www.tri-star.co.in)

## TRI-LDC-N-TS2

### Introduction:

The TRI-LDC-N-TS2 is Tristar's newest generation of video wall splicer, featuring excellent image quality and designed especially for fine-pitch LED screens. The TRI-LDC-N-TS2 can work as splicing processors that integrate both video processing and video control capabilities or work as pure splicing processors. The whole unit adopts a modular and plug-in design and allows for flexible configuration and hot swapping of input and output cards. Thanks to excellent features and stable performance, the TRI-LDC-N-TS2 can be widely used in a variety of applications, such as energy and power, judicial departments and prisons, military command, water conservancy and hydrology, meteorologic earthquake prediction, enterprise management, metallurgy of steel, banking and finance, national defense, public security traffic management, exhibitions and presentations, production scheduling, radio and television, educational and scientific research, as well as stage rental applications.

### Features :

- ☐ Simple screen configuration using a single card and connector.
- ☐ Online status monitoring of all input and output cards
- ☐ Hot-swappable input and output cards
- ☐ 2xRJ45 IP input card supports up to 512 IP camera inputs and input mosaic.
- ☐ Auto decryption of HDCP-encrypted sources
- ☐ Decimal frame rates supported.
- ☐ HDR10 and HLG processing
- ☐ Input source grouping management
- ☐ Eye saver mode Display the image in a warmer but less bright way to relieve eye strain.
- ☐ LCD bezel compensation
- ☐ Multi-screen management and operations Centralized management of multiple screens, such as preset group management, freezing, FTB, screen locking and brightness adjustment.
- ☐ Configure signal source playback and use the source playback group as a layer source.

\* Note: These specifications are subject to change without any prior notice.

### **Technical parameters - TRI-LDC-N-TS2:**

<b>Model</b>		TRI-LDC-N-TS2
<b>Rack Unit</b>		2U
<b>Max. Input Cards (supported)</b>		4
<b>Max. Input Channels (supported)</b>		16
<b>Max. Output Cards (supported)</b>		2
<b>Max. Output Channels (supported)</b>		8
<b>Max. Loading Capacity</b>	16xRJ45+2xfiber sending card	20.8 million pixels
	20xRJ45 sending card	26 million pixels
	4xfiber sending card	41.6 million pixels
<b>Max. Layers</b>		32
<b>Electrical Specifications</b>	Power connector	100–240V~, 50/60Hz, 4.0A
	Power consumption	210 W
<b>Operating Environment</b>	Temperature	0°C to 45°C
	Humidity	0% RH to 80% RH, non-condensing
<b>Storage Environment</b>	Temperature	–10°C to +60°C
	Humidity	0% RH to 95% RH, non-condensing
<b>Physical Specifications</b>	Dimensions	482.6 mm × 529.8 mm × 88.1 mm
	Net weight	11 kg (chassis)
	Gross weight	12.2 kg (chassis)
<b>Noise Level (typical at 25°C /77°F)</b>		<45 dB (A)
<b>Packing</b>	<b>Packing box</b>	660 mm × 570 mm × 210 mm

\* Note: These specifications are subject to change without any prior notice.

<b>Information</b>	<b>Accessories</b>	1x Power cord 1x RJ45 Ethernet cable 1x Grounding cable 1x HDMI cable 1x Quick Start Guide 1x Certificate of Approval 1x Safety Manual
		1x Custom Letter

\* Note: These specifications are subject to change without any prior notice.