

Indoor LED Video Wall

TRI-VW-SID-HPS-1.56

Large venues | Live events & performing arts | Auditorium | planetarium | Network Operation Centers

Features:

Various panel sizes :

- 500x500/750/1000x40mm; 1000/750/500x250x40mm
- All sizes can be mixed splicing

Flexible Splicing :

- Mal-posed splicing/90° Rotated splicing/
- Right angle/Concave & Convex

Wireless connect between modules and cabinet

Front and Rear maintenance

Wall mounting/ Back-strip/Hanging/Stacking Installation.



TRI-VW-SID-HPS-1.56

Technical specifications

Parameter	Value
LED Type	1212
Pixel Density	409600
Panel Size (mm)	500 x 500/750/1000 x 40 & 500/750/1000 x 250 x 40
Panel Weight (Kg/panel)	4.9/6.1/9.2 & 2.5/3.6/5.2
Module Size (mm)	250 x 250
Module Weight(Kg/pc)	0.41
Color Grayscale (Bit)	≥14
Refresh Rate (Hz)	≥3840
Brightness (nits)	800
Contrast Ratio	5000:1
Material	Die Casing Aluminum
AC Input Power Max/Ave (W/m ²)	435/145 ± 10%W/m ²
Horizontal / Vertical Viewing Angle	155° / 155°
Maintenance	Front & Rear
Installation	Wall mounting / Back-strip / hanging / Stacking
Certification	BIS