


TRISTAR



www.tri-star.co.in

TRI-VW-SID-HPS SERIES

Product Specifications:

- ☐ Golden Ratio 16:9 Display Configuration
- ☐ Highly Integrated System Architecture
- ☐ Large Curvature: Right-Angle/Concave Options
- ☐ Wireless Connectivity Modules
- ☐ Front Maintenance
- ☐ Intelligent Module Integration (Optional)
- ☐ Dual Backup System (Optional)
- ☐ GOB Technology Integration (Optional)



Technical parameters- TRI-VW-SID-HPS-1.8

Parameter	Value
Pixel Pitch	1.8mm
LED Type	SMD1515
Brightness	600cd/m ²
Panel Size	600x337.5x45mm
Panel Weight	4kg/panel
Module Size	150×337.5mm
Pixel Density	284445pixels/m ²
Pixels Per Panel	320x180pixels
Maintenance	Front
Ingress Protection	Rear IP30
Pixel configuration	3 in 1 configuration
Curve	Customized according to customers' needs
Panel Area	0.2025 m ²
Environment	Indoor
Material	Die-cast Aluminum
Calibration	Support brightness and chroma
Color Temperature	2,000K~9,300K Adjustable
Horizontal Viewing Angle	160°
Vertical Viewing Angle	160°
Contrast Ratio	5000:1
Input Power <Max>	120±10%W/Panel
Input Power <Typical>	40±10%W/Panel
Input Voltage	100~240VAC
Processing Depth	≥14bit
Refresh Rate	≥3840Hz
Video Frame Rate	50&60Hz
Input Power Frequency	50~60Hz
LED Life Time	100,000 Hours
Operating Temperature/Humidity	-10°C~+45°C/10~70%RH
Storage Temperature/Humidity	-20°C~+55°C/10~80%RH
Standard Mounting Configuration	Fixed
Certification	BIS

* Note: These specifications are subject to change without any prior notice.