

Outdoor LED Video Wall

TRI-VW-SOD-TST-10.0

Large venues | Live events & performing arts | Auditorium | planetarium | Network Operation Centers

Features:

- 6000 – 10000nits brightness
- 14bit grayscale
- 7680HZ refresh rate.
- P4 / 4.44 / 6.67 / 8 / 10 available
- Higher contrast, max 40000: 1*
- Efficient Heat dissipation with multiple special design
- Superior Waterproof performance-IP65
- Stable structure and better structural strength



TRI-VW-SOD-TST-10.0

Technical specifications

Parameter	Value
Pixel Configuration	SMD2727
Pixel Pitch (mm)	10
Pixel density (pixels/sq.m.)	10000
Cabinet Dimensions (WxHxD)/(mm)	960x960x91
Module Dimensions (WxH)/(mm)	480X320
Cabinet weight (kg/panel)	25
Color Grayscale (Bit)	14bit
Refresh Rate (Hz)	3840-7680
Brightness (nits)	6000-10000
Optimal Horizontal Viewing Angle (°)	160
Optimal Vertical Viewing Angle (°)	Up50/Down60
Contrast ratio	8400-40000:1
AC Input Power Maximum Value (W/m2)	600-710s
AC Input Power Typical Value (W/m2)	200-240
IP rating (Front/Rear)	IP65/IP65
Certification	BIS

For the most current specification information, please visit tri-star.co.in