



www.tri-star.co.in

TRI-VW-SOD-TST SERIES:



Features :

- **Fanless design reduces both noise and screen failure rate during operation.**
- **Excellent heat dissipation design improves the heat dissipation capacity. Therefore, it can ensure that the product is more durable and stable during operation.**
- **Add convenient handle design:Hidden red handles on both sides,facilitates worker handling with fewer unnecessary risks.**
- **Rear maintenance cabinet, bilateral door design, more operating space, convenient and fast maintenance.**
- **Good Compatibility**

* Note: These specifications are subject to change without any prior notice.

Technical parameters-TRI-VW-SOD-TST-2.5:

Parameter	Value
LED	SMD1415
Module Resolution (W×H)	128*64
Cabinet Dimension(W×H×D) mm	640mm*640mm*79mm
Cabinet Resolution (W×H)	256*256
Maintenance	Full rear maintenance
Material	Die-casting Aluminum/Magnesium
Cabinet Weight(kg/panel)	12.5
Refrequency (Hz)	60 HZ
RefreshRate (Hz)	3840Hz
Processing Depth	12~14bit
White Balance Brightness	4000~4500cd/m ²
Standard Color Temperature	2000K~9300K adjustable
Beam Angle (Hor/Ver°)	160°/140°
Contrast Ratio	5000:1
Input Power <Max>	879W/m ²
Input Power <Typical>	264W/m ²
Power Supply Input Voltage	AC200-240V, 47-63(Hz)
Life Span	100000Hrs
Working Temperature/ Humidity Range	-20°C~+50°C/10%~80%RH (NoCondensation)
Storage Temperature / Humidity Range	-20°C~+55°C/10%~85%RH (NoCondensation)
ProtectionGrade (Front/Rear)	IP65(Front), IP54(Rear)
Certification	BIS

* Note: These specifications are subject to change without any prior notice.