

## Outdoor LED Video Wall

TRI-VW-SOD-TST-5.0

Large venues | Live events & performing arts | Auditorium | planetarium | Network Operation Centers

### Features:

- Fanless design reduces both noise and screen failure rate during operation.
- Excellent heat dissipation design improves the heat dissipation capacity. Therefore, it can ensure that the product is more durable and stable during operation.
- Add convenient handle design: Hidden red handles on both sides, facilitates worker handling with fewer unnecessary risks.
- Rear maintenance cabinet, bilateral door design, more operating space, convenient and fast maintenance.
- Good Compatibility



## TRI-VW-SOD-TST-5.0

### Technical specifications

| Parameter                            | Value                                  |
|--------------------------------------|----------------------------------------|
| LED                                  | SMD2727                                |
| Module Resolution (W×H)              | 64x32                                  |
| Cabinet Dimension(W×H×D) mm          | 960mm*960mm*125mm                      |
| Cabinet Resolution (W×H)             | 192*192                                |
| Maintenance                          | Full rear maintenance                  |
| Material                             | Die-casting Aluminum/Magnesium         |
| Cabinet Weight(kg/panel)             | 26.5                                   |
| Refrequency (Hz)                     | 60 HZ                                  |
| RefreshRate (Hz)                     | 3840Hz                                 |
| Processing Depth                     | 12~14bit                               |
| White Balance Brightness             | 5000~5500cd/m2                         |
| Standard Color Temperature           | 2000K~9300K adjustable                 |
| Beam Angle (Hor/Ver°)                | 160°/140°                              |
| Contrast Ratio                       | 5000:1                                 |
| Input Power <Max>                    | 879W/m <sup>2</sup>                    |
| Input Power <Typical>                | 264W/m <sup>2</sup>                    |
| Power Supply Input Voltage           | AC200-240V, 47-63(Hz)                  |
| Life Span                            | 100000Hrs                              |
| Working Temperature/ Humidity Range  | -20°C~+50°C/10%~80%RH (NoCondensation) |
| Storage Temperature / Humidity Range | -20°C~+55°C/10%~85%RH (NoCondensation) |
| ProtectionGrade (Front/Rear)         | IP65(Front), IP54(Rear)                |
| Certification                        | BIS                                    |

For the most current specification information, please visit [tri-star.co.in](http://tri-star.co.in)