

Digital Voting Chairman Unit with Channel Selector

TRI-ACV-MC-4016

Large venues | Live events & performing arts | Auditorium | planetarium | Network Operation Centers

Features:

- Stylish, low-profile design with touchable interface
- Standard CAT5e and RJ45 connectors are used in CCON series to provide more convenient on project and maintenance.
- The connection cable of units are either hiding underneath or from the rear of the unit, makes it convenient for different request of installation
- OLED screen, providing excellent brightness, contrast, wide viewing angle but low power consumption.
- Internal high-fidelity loudspeaker
- Built-in interpretation channel selector
- Head-set interface in both sides with volume adjust.

Functions:

- Compliance with IEC 60914, GBT 15381-94
- The unique AUDIO-LINK digital ring network technology achieve full-digital signal transmission and processing, completely avoid the RF interference from cell phone or similar devices.
- Single CAT5e cable transmits 64 channels of audio and various information.
- High fidelity sound by zero loss audio transmit technology, 48K audio sampling frequency, 20Hz~20KHz response frequency.
- "Hand-in-Hand-Loop-Network" connection makes the system always working perfectly no matter changing discussion unit or having any malfunctioned units



TRI-ACV-MC-4016

Technical specifications

Parameter	Value
Button	Touchable interface
Sound Pickup	heart type capacitance
Display	OLED display 128 × 32
Sensitivity	-46 dBV / Pa
Maximum power consumption	2.0W
Directivity	0 ° / 180 °> 20 dB (1 kHz)
Headphone load	16Ω
volume	10mW
Headphone jack	3.5mm stereo
Input impedance	2kΩ
SNR	70dB
Frequency response	20 ~ 20000Hz
Connection	CAT5 / CAT6 cable + snap
Equivalent noise	20dBA (SPL)
Main material	ABS
The maximum sound pressure	125dB (THD <3%)
Weight	1.1kg (with microphone)
Dimension	195L × 120W× 60H mm (without microphone)
Operating temperature	0 °C to + 55 °C
Color	Black
Certification	BIS