



www.tri-star.co.in

TRI-AVC-HSE4K-R-5003

HDMI 4k Receiver:



Technical parameters - TRI-AVC-HSE4K-R-5003:

Input Interface	Rj45 Connector 7
Output Interface	HDMI-A Interface
Supported Protocols	HDMI 1.4a, HDCP1.3, HDCP2.2, EDID 1.4
Pixel Bandwidth	More Than 225mhz, Full Digital
Interface Bandwidth	More Than 6.75gbps
Supported Resolution	1080p/60 Deep Color Upto 3840 X 2160 / 30 Hz
Signal Type	HDMI I.4a/T.M.D. S Full Digital Signal
Signal Strength	T.M.D.S. +/-0.4 Vpp
Minimum/ Maximum Level	T.M.D.S. 2.9v/3.3v
Audio Input	HDMI & Analog
Impedance	The Difference Of 100
Serial Port Control	Rs-232 (BI Directional)
Baud Rate	Maximum 5mv
Infrared Control	Ir 3.5mm
Ir Frequency	38khz
Maximum Distance	100 Meter Through CAT6
Remote Power	Support POC (Power Over Cable) function, it means that either the transmitter or receiver is connected to 12V/1A power supply, the other doesn't need power supply

* Note: These specifications are subject to change without any prior notice.